

Pos	Brennertyp	Max. Ausgangsstrom		Einstufung		Drahtdurchmesser		Schocksensor			Kühlsystem	Bemerkung
		CO2	MAG	CO2	MAG	Standard	Verfügbar	SSV	SSB	eingebaut		
1	RT3500S	350 A	350 A	80 %	60 %	Fe 1.2	0,8-1.6	x			luftgekühlt	
2	RT3500H	350 A	350 A	80 %	60 %	Fe 1.2	0,8-1.6	x	x		luftgekühlt	
3	RT3500L	350 A	350 A	80 %	60 %	Fe 1.2	0,8-1.6	x	x		luftgekühlt	
4	RT5000S	500 A	350 A	50 %	70 %	Fe 1.2	0,8-1.6	x			luftgekühlt	
5	RT5000H	500 A	350 A	50 %	70 %	Fe 1.2	0,8-1.6	x	x		luftgekühlt	
6	RT5000L	500 A	350 A	50 %	70 %	Fe 1.2	0,8-1.6	x	x		luftgekühlt	
7	RZ3500S	350 A	350 A	80 %	60 %	Fe 1.2	0,9-1.6	x			luftgekühlt	
8	RZ3500H	350 A	350 A	80 %	60 %	Fe 1.2	0,9-1.6	x	x		luftgekühlt	
9	RZ3500L	350 A	350 A	80 %	60 %	Fe 1.2	0,9-1.6	x	x		luftgekühlt	
10	RTW5000S	500 A	400 A	70 %	60%	Fe 1.6	1.2-1.6	x			wassergekühlt	
11	RTW5000H	500 A	400 A	70 %	60%	Fe 1.6	1.2-1.6	x	x		wassergekühlt	
12	RTW5000L	500 A	400 A	70 %	60%	Fe 1.6	1.2-1.6	x	x		wassergekühlt	